



## Product Code

**ECS303G-4.5-L**

- ◆ Chopped Strand
- ◆ Sizing Agent Code
- ◆ Cut Length
- ◆ Fiber Diameter

ECS303G is specially designed to enhance PBT resin systems and is also suitable for PBT, PET, and their blends or alloys with other plastics. Thanks to our unique surface treatment technology, composite products manufactured with this material exhibit excellent mechanical properties, good boiling water resistance, and a whiter color.

Product Features	Technical Specifications			
<ul style="list-style-type: none"><li>Good dispersibility</li><li>High mechanical performance</li><li>Excellent process operability</li><li>Good resin compatibility</li></ul>	Filament Diameter [ $\mu\text{m}$ ]	Loss On Ignition[%]	Moisture Content[%]	Strand Integrity[g]
	ISO 1888	ISO 1887	ISO 3344	*Q/CPIC TM-13
	14±1	0.75±0.15	≤0.10	≤10

## 规格型号 Specification

Product Code	Glass Type	Fiber Diameter [ $\mu\text{m}$ ]	Cut Length [mm]
ECS303G-4.5-L	E、ECT	14	4.5

## 包装与储存 Packaging & Storage

Packaging	Nominal Weight[kg]	Quantity per Pallet[个]	Pallet dimensions[mm]
Bulk bag	1000	1	1140*1140*1160
bags of paper	25	40	1140*1140*830

Please store the glass fiber products in a dry and cool environment, with recommended temperature control between 10-30° C and humidity control between 50-75%. The product must remain in its sealed packaging until use. Pallet stacking height should not exceed one layer.

