



Product Code

ECT4305-2400

- ◆ Glass Type
- ◆ Sizing Agent Code
- ◆ Roving Linear Density (Tex)

4305 is an ECT-glass-based direct roving manufactured with fluorine- and boron-free composition, fully compliant with REACH regulations, and featuring high chromatic stability. Treated with a specialized sizing agent, it delivers exceptional compatibility with polypropylene (PP) resin.

Product Features		Technical Specifications			
● Excellent dispersion ● low fuzz generation, ● compatibility with multiple downstream processes ● excellent mechanical properties	Fiber Diameter [μm]	Loss on ignition[%]	Moisture Content[%]	Tensile Strength[N/Tex]	
	ISO 1888	ISO 1887	ISO 3344	ISO 3341	
	16±1	0.15-0.45	≤0.10	≥0.25	

規格型号 Specification

Product Code	Glass Type	Fiber Diameter [μm]	Linear Density (Tex) [g/km]
ECT4305-2400	ECT	16	2400

包装与储存 Packaging & Storage

Packaging Method	Net Weight per Roll [kg]	Quantity per Pallet [个]	Pallet dimensions [mm]
Pallet Packaging	18-24	48	1140*1140*960
		64	1140*1140*1200
		36	950*1280*960
		48	950*1280*1200

Please store the glass fiber products in a dry and cool environment, with recommended temperature control between 10-30° C and humidity control between 50-75%. Stack pallets no more than 2 layers high.

