



Product Code

ECS303W-3-H

- ◆ Chopped Strand
- ◆ Sizing Agent Code
- ◆ Cut Length
- ◆ Fiber Diameter

ECS303W is a chopped fiber specifically designed for reinforcing thermoplastic plastics, featuring precision surface treatment with advanced silane-based sizing agents. As a universal modified standard product for PET, PBT, and PC, it exhibits excellent yellowing resistance at high temperatures. Widely used in home appliances, electronics, machinery manufacturing and other fields, the product is guaranteed to be free of NPE.

Product Features

- Good dispersibility
- High mechanical properties
- Excellent yellowing resistance
- Good resin compatibility

Technical Specifications

<ul style="list-style-type: none">● Good dispersibility● High mechanical properties● Excellent yellowing resistance● Good resin compatibility	Filament Diameter [μm]	Loss On Ignition [%]	Moisture Content [%]	Strand Integrity [g]
	ISO 1888	ISO 1887	ISO 3344	*Q/CPIC TM-13
	10±1	1.25±0.15	≤0.05	≤25

规格型号 Specification

Product Code	Glass Type	Fiber Diameter [μm]	Cut Length [mm]
ECS303W-3-H	ECT	10、13	3

包装与储存 Packaging & Storage

Packaging	Nominal Weight [kg]	Quantity per Pallet [个]	Pallet dimensions [mm]
Bulk bag	1000	1	1140*1140*1160
bags of paper	25	40	1140*1140*830

Please store the glass fiber products in a dry and cool environment, with recommended temperature control between 10-30° C and humidity control between 50-75%. The product must remain in its sealed packaging until use. Pallet stacking height should not exceed one layer.

