



Product Code

ECS304A-3-H

- ◆Chopped Strand
- ◆Sizing Agent Code
- ◆Cut Length
- ◆Fiber Diameter

ECS304A is a chopped fiber specially designed for reinforcing thermoplastic plastics. It undergoes precise surface treatment with advanced silane-based sizing agents, making it a standard modified product specifically for AS/ABS applications. It features excellent processability and is widely used in various fields including transportation, electrical appliances, and machinery manufacturing.

| Product Features | Technical Specifications | | | |
|--|--------------------------|---------------------|---------------------|---------------------|
| <ul style="list-style-type: none">Excellent production stabilitySuperior bundle integrityOutstanding mechanical strength | Filament Diameter [μm] | Loss On Ignition[%] | Moisture Content[%] | Strand Integrity[g] |
| | ISO 1888 | ISO 1887 | ISO 3344 | *Q/CPIC TM-13 |
| | 13±1 | 0.75±0.10 | ≤0.05 | ≤5 |

| 规格型号 Specification | | | |
|--------------------|------------|---------------------|-----------------|
| Product Code | Glass Type | Fiber Diameter [μm] | Cut Length [mm] |
| ECS304A-3-K | ECT | 13 | 3 |

| 包装与储存 Packaging & Storage | | | |
|---------------------------|--------------------|------------------------|-----------------------|
| Packaging | Nominal Weight[kg] | Quantity per Pallet[个] | Pallet dimensions[mm] |
| Bulk bag | 1000 | 1 | 1140*1140*1160 |
| bags of paper | 25 | 40 | 1140*1140*830 |

Please store the glass fiber products in a dry and cool environment, with recommended temperature control between 10-30° C and humidity control between 50-75%. The product must remain in its sealed packaging until use. Pallet stacking height should not exceed one layer.