



Product Code

ECS3014B-3-H

- ◆Chopped Strand
- ◆Sizing Agent Code
- ◆Cut Length
- ◆Fiber Diameter

ECS3014B is primarily suitable for low-viscosity resins such as PA66, PA6, PA46, and elastomer-modified nylon systems. Composite products manufactured using this material exhibit excellent mechanical properties, high dispersion performance, and low yellowing.

Product Features	Technical Specifications			
- Proprietary Surface Treatment Technology - Good dispersibility - Superior processability - Superior bundle integrity	Filament Diameter [μm]	Loss On Ignition[%]	Moisture Content[%]	Strand Integrity[g]
	ISO 1888	ISO 1887	ISO 3344	*Q/CPIC TM-13
	10±1	0.60±0.10	≤0.05	≤5

规格型号 Specification			
Product Code	Glass Type	Fiber Diameter [μm]	Cut Length [mm]
ECS3014B-3-H	ECT	10、13	1.7、3、4.5

包装与储存 Packaging & Storage			
Packaging	Nominal Weight[kg]	Quantity per Pallet[个]	Pallet dimensions[mm]
Bulk bag	1000	1	1140*1140*1160
bags of paper	25	40	1140*1140*830

Please store the glass fiber products in a dry and cool environment, with recommended temperature control between 10-30° C and humidity control between 50-75%. The product must remain in its sealed packaging until use. Pallet stacking height should not exceed one layer.

