



Product Code

ECS309C-3-H

- ◆ Chopped Strand
- ◆ Sizing Agent Code
- ◆ Cut Length
- ◆ Fiber Diameter

ECS309C is a chopped fiber specifically designed for reinforcing thermoplastic plastics, serving as a PPS-dedicated modified product while also being suitable for amorphous PPA. ECS309C not only excels in enhancing overall material strength and rigidity, but also meets customer requirements for water-boiling resistance. It is widely used in transportation, electrical appliances, and other fields. The product is FDA-certified and guaranteed to be free of NPE.

Product Features	Technical Specifications			
<ul style="list-style-type: none">Excellent dispersibilityExcellent resistance to water boilingUltra-low smoke emissionGood process operability	Filament Diameter [μm]	Loss On Ignition[%]	Moisture Content[%]	Strand Integrity[g]
	ISO 1888	ISO 1887	ISO 3344	*Q/CPIC TM-13
	10 \pm 1	0.35 \pm 0.10	\leq 0.10	\leq 15

规格型号 Specification			
Product Code	Glass Type	Fiber Diameter [μm]	Cut Length [mm]
ECS309C-3-H	E、ECT	10	3

Packaging	Nominal Weight[kg]	Quantity per Pallet[个]	Pallet dimensions[mm]
Bulk bag	1000	1	1140*1140*1160
bags of paper	25	40	1140*1140*830

Please store the glass fiber products in a dry and cool environment, with recommended temperature control between 10-30° C and humidity control between 50-75%. The product must remain in its sealed packaging until use. Pallet stacking height should not exceed one layer.

